## **Technical Data Information Report**

recrimed Bata infermation report							
RID Number 7908.00	Transmitter	Transmitter Organization  Nye County NWRPO	Receiver QARC	Receiver Organization  Nye County NWRPO	Keyword 1 GWE	_	
7906.00	Howard	Nye County NVVKPO	QARC	Nye County NVVKPO	GWE		
Document Date	1/11/2011	General Docume	ent Type	QA Program Doc	Keyword 2	Drilling	
Entry Date	3/15/2011	Detail Document Type		Well Completion Diagram	Keyword 3	Completion	
Document Title/Subject	NC-GWE-GF-4PA Well Completion Diagram.						
Data Originator/Preparer	Kathy Gilmo	Kathy Gilmore					
Data Description	and GWE_G	Well Completion Diagram for well NC-GWE-GF-4PA. Package contains hardcopy and electronic formats in DWG and PDF files: GWE_GF_4PA_WCD.dwg and GWE_GF-4PA_WCD.pdf. As-built diagrams are in hardcopy form. Updated Well Completion Diagram for consistency and readability. Package also contains Wellhead Protection detail in hardcopy form. File GWE_GF_4PA_WCD.pdf is posted to the NWRPO website as rid7908.pdf					
Data Collection Method	Data collected during well completion activities at site NC-GWE-GF-4PA.						
Data Collection Location	NC-GWE-G	NC-GWE-GF-4PA.					
Data Collection Period	1/11/2011						
Data Sources	Tubing and	Tubing and Casing Records and Scientific Notebook # 179 pages 144, 148 through 149.					
Data Censoring	None						
Data Processing	None						
Data Limitations	Borehole, casing and tubing depths are determined through direct measurement of drill pipe, well casing and tubing strings that are recorded on Tubing and Casing Records. All depths below original ground level were made in reference to a ground level datum or benchmark pin that was driven into undisturbed soils near the borehole prior to drilling. All depths and stick-up measurements are relative to this datum. Depths of completion materials (sand, grout, and other completion materials) are determined by "tagging" the depth of the emplaced material with a wireline tagging tool. The field accuracy of the tag tool is considered to be +/- 1 ft beyond 1000 ft and +/- 0.5 ft at a depth less than 1000 ft. Depths are not corrected for borehole deviation.						
Governing QA Docs:	TPN-5.6, Rev. 0						
Frequency of Transmittal	Once per bo	Once per borehole/well.					
Direct Questions About Data To:	NWRPO QA Records Center						

Friday, April 15, 2011 Page 1 of 1